

# Technical Specifications

## clocetex Flocked Carpet data sheet

No.	Item	Standard	Requirement	Results
1	섬유 혼용율 (Fiber composition)	KS K 0210	Nylon66 100%	
2	폭 및 길이 (Tile size)	KS K 1417	500X500 (mm)	
3	직각정도 (Squareness of edge)	KS K 1417	< 0.1%	
4	바퀴의자시험 (Castor chair test)	KS K 1417	< 0.15%	
5	치수안정성 (Dimensional stability)	KS K 1417	< 0.10%	
6	말림 (Curing/Doming)	KS K 1417	< 1.5mm	
7	일광견뢰도 (Light fastness)	KS K ISO 105-B02	> 5	
8	마찰견뢰도 (Rubbing fastness)	KS K ISO 105-X12	> 4	
9	물견뢰도 (Water fastness)	KS K ISO 150-E01	> 4	Pass
10	박리저항성 (Delamination resistance)	KS K 1417	> 50mm 당 40N	
11	대전성 (Body voltage)	KS K 1417	< 2.0 KV	
12	불투수성 (Water impermeability)	KS K 1417	물 침투 흔적 없을 것	
13	난연성 (Flame resistance)	KS K 1417	탄화길이 : < 10cm 잔염시간 : < 20초	
14	파일사 용제 추출분 (Solvent Extractables of fiber)	KS K 1417	< 0.9%	
15	미끄럼저항성 (Slip resistance)	KS M 3510	DS : > 0.30	
16	소음저감 (Acoustical impact noise reduction)	KS K ISO 717-2	$\Delta Lw = 22dB$	
17	항균성 (antibacterial)	KS K 0693	99.9%	